

Magela Creek monitoring data 2019-2020

The Supervising Scientist's water chemistry monitoring program has been developed using continuous monitoring of physico-chemical parameters coupled with automatic event-based collection of water samples. Chemistry samples are collected when an electrical conductivity (EC) trigger is reached, indicating the potential for high concentrations of contaminants to be present in the creek, and also during routine monthly quality assurance sampling. No event-based samples were collected during the 2019/20 wet season due to the low electrical conductivity.

Details regarding the development and operation of the monitoring program can be found in the <u>Surface water chemistry monitoring protocol to assess impacts from Ranger Mine.</u>

The charts below compare measurements of key chemical indicators, collected during the **2019-2020** wet season, to the <u>Water Quality Objectives (WQOs</u>) for Magela Creek. The WQOs present a hierarchical set of trigger values for each indicator, enabling a tiered approach to the oversight and management of water quality in Magela Creek.

Focus Trigger Value - Values that are higher than the Focus level but lower than the Action level will result in a watching brief. A watching brief involves precautionary ongoing data assessment to verify whether or not a trend away from background is occurring, possibly including further sampling if required.

Action Trigger Value - Values that are higher than the Action level but lower than the Guideline/Limit will result in a data assessment. Where assessment of the data shows the value represents a trend away from background the company must undertake:

- An investigation into the cause of the exceedance; and
- Correction of the cause if it is deemed to be mining related.

The Focus and Action Trigger Values are used by the company to manage surface water quality during mine activities. These are not displayed on the charts below.

Guideline Trigger Value - The company shall treat values in excess of the Guideline the same as a Limit exceedance except:

- When there is a corresponding increase at the upstream site; and
- For the Mn limit when the flow is less than five cumecs.

When one or more of the above exceptions occurs, a Guideline exceedance will be treated the same as an Action exceedance.



Limit Trigger Value - Values that are higher than the Limit will result in a full investigation, including:

- Determining the cause(s) of the exceedance;
- Collecting further samples and data; and
- Undertaking immediate correction of the cause if it is deemed to be mining related.

The Guideline and/or Limit Values are used to monitor compliance and ensure the protection of the downstream environment.

Flow commenced in Magela Creek 10th January 2020. Rainfall during the 2019/2020 wet season, as recorded at Jabiru Airport, has been below average totaling 900mm. The last rainfall recorded at Jabiru Airport was on 22nd June 2020, and was 0.6mm. Flow ceased in Magela Creek 19th June 2020.

Water quality monitoring data collected by the SSB to date show that all Water Quality Objectives were met in Magela Creek for the 2019/2020 wet season, indicating that operations at Ranger mine have not resulted in harm to downstream environments.

Chemical Indicators

- Conductivity in Magela Creek
- Magnesium in Magela Creek
- Uranium in Magela Creek
- Manganese in Magela Creek
- Total Ammonia Nitrogen (TAN) in Magela Creek
- Turbidity in Magela Creek
- Radium-226 in Magela Creek



Conductivity in Magela Creek

A set of Electrical Conductivity (EC) Trigger Values has been derived to indicate when magnesium (Mg) concentrations might be approaching levels that exceed the Mg Trigger Values. The EC Trigger Values are essentially the same as the Mg Trigger Values, converted to EC using the long term EC-Mg relationship for Magela Creek. An additional *Investigation Trigger* was derived for EC which prompts an assessment of estimated Mg concentrations using the long-term Mg/EC relationship or an event specific relationship. The EC *Investigation Trigger* applies if conductivity exceeds 42 μ S/cm for more than 6 hours to prevent unnecessary action for short duration (<6 hours) pulses that go above 42 μ S/cm but do not approach the Mg Guideline value.

To the end of the wet season, the conductivity in Magela Creek remained below the Investigation trigger value.



Magela Creek continuous conductivity monitoring data for 2019/2020 wet season



Magnesium in Magela Creek

The magnesium *Chronic Exposure Limit* of 3 mg/L has been derived using local ecotoxicological data and applies to exposures greater than 72 hours in duration. The Supervising Scientist has also developed an interpretative framework for Mg exposures of less than 72 hours, which integrates the magnitude and the duration of any given pulse exposure. Details can be found in the <u>Revised Ranger Mine Water Quality Objectives for Magela Creek and Gulungul Creek.</u>

The EC trace indicates that magnesium has been below the Chronic Exposure Limit through to the end of the wet season. Discrete samples collected from downstream Magela Creek confirmed this interpretation with magnesium concentrations below the limit.



Magela Creek magnesium data for the 2019/2020 wet season (continuous EC data shown in background for reference)



Uranium in Magela Creek

The uranium *Limit Trigger Value* of 2.8 μ g/L has been derived using local ecotoxicological data in accordance with the Australian Water Quality Guidelines to protect 99% of the species present.

The uranium concentration in samples collected to the end of the wet season were low and well below the trigger value at the Magela Creek downstream site.



Magela Creek uranium data for the 2019/2020 (continuous EC data shown in background

for reference)



Manganese in Magela Creek

The manganese *Limit Trigger Value* of 75 μ g/L has been derived using local ecotoxicological data and applies to creek flows greater than 5 cumecs. Flows less than 5 cumecs are indicative of groundwater-dominated inputs, which are likely to be higher in manganese. This guideline may be exceeded occasionally due to natural events but should not be exceeded due to mining activities.

The manganese concentrations in samples collected to the end of the wet season were low and below the limit trigger value at the Magela Creek downstream site.



Magela Creek manganese data for the 2019/2020 wet season (continuous EC data shown in background for reference)



Total Ammonia Nitrogen (TAN) in Magela Creek

The interim total ammonia nitrogen (TAN) *Guideline Trigger Value* of 0.7 mg/L was derived using international ecotoxicity data. In accordance with the Australian Water Quality Guidelines, the Supervising Scientist is currently developing site-specific trigger values, based on ecotoxicity data using local aquatic species.

The TAN concentration in samples collected to the end of the wet season were well below the guideline trigger value at the Magela Creek downstream site.



Magela Creek total ammonia nitrogen (TAN) data for the 2019/2020 wet season (continuous EC data shown in background for reference)



Turbidity in Magela Creek

The turbidity *Guideline Trigger Value* of 26 NTU was determined statistically from historical weekly grab sampling data, and applies to water quality measured in grab samples. This guideline may be exceeded occasionally due to natural events but should not be exceeded due to mining activities.

The turbidity values recorded in Magela Creek were mainly below the guideline value to the end of the wet season. Peaks in turbidity in January were associated with first flows and rainfall events, and were detected at both upstream and downstream monitoring sites. These peaks do not reflect a trend of increased turbidity at the downstream site, or mining-related effects.



Magela Creek continuous turbidity monitoring data for the 2019/2020 wet season



Radium-226 in Magela Creek

The activity concentration limit for radium-226 was developed to ensure the radiation dose received by people who consume mussels from downstream waterways remains safe. The radium-226 Limit *Trigger Value* of less than 3 mBq/L is calculated as the geometric mean difference between the upstream and downstream values for the entire wet season.

Radium-226 samples collected and reported during the wet season are within historical ranges at both the upstream and downstream sites. The geometric mean difference for the entire wet season is below the limit trigger value.

